



## Marla DELIBLACK

Item number 21907, KMAT 61000211



### Product description

Blackouts have a blackout level of 100%. Thanks to an acrylate soft coating on the back, light rays cannot penetrate the material. The coating is particularly soft, which is why the fabric retains its flowing drape. All items in the Blackout range also have special stain protection and are naturally flame-retardant. Marla is a high-quality blackout with an extremely soft feel and a gray reverse side. The use of colorful yarns, which create a two-tone changeant effect, gives Marla an extraordinary character. The resulting sheen is elegant, the colorfulness special. A total of 13 colors are available.

### Technical Details

|  |  |
|--|--|
| <b>Fabric width</b>  | approx. 290 cm   |
| <b>Weight je m<sup>2</sup></b>   | approx. 290 g/m <sup>2</sup>   |
| <b>Composition</b>   | 100% Polyester Acrylat Softbeschichtung  |
| <b>Flame retardancy</b>  | IMO 2010 FTP Code Part 7, M 1, C 1, BS 5867 Typ B, EN 13773, DIN 4102 / B1, DIN 4102 / B2, NFPA 701<br>Flammability performance is dependant on the foam used. |
| <b>Light fastness</b>  | note 5-6   |
| <b>Light &amp; solar properties</b>  | {"color": "3001", "total_energy_permeability_degree": 0.59, "reduce_factor": 0.77}   |
| <b>Wash fastness 40°C<br/>DIN EN ISO 105-C06</b>                           | note 5   |
| <b>Dimensional change Washing 40°C<br/>DIN EN ISO 6330 DIN EN ISO 5077</b> | warp approx. +/-1%, weft approx. +/-1%   |

---

**Rubbing fastness**  
**DIN EN ISO 105-X12**

dry: note 4-5, wet: note 4-5

---

**Care labelling**



---

**Additional information**

Nur die unbeschichtete Seite bügeln!

---

**State**

2024-04-23