

Intertek The Warehouse Brewery Lane Leigh WN7 2RJ UK Tel +44 1942 265 700 consumergoods.uk@intertek.com intertek.com

FLAMMABILITY TEST REPORT

Report No.: LEI19011658A Supplementary	Date Received: 10/01/19	Date Tested: 14/01/19	1 st Date Issued: 14/01/19 Supplementary Issued: 04/02/19	
Company Name & Address:	DELIUS GMBH & CO. GOLDSTRAßE 16-18 33602 BIELEFELD GERMANY	KG		
Contact Name:	P. BAUMHÖFNER			
Sample Details				
Reference No.:	Not stated			
Order No.:	665			
Style No.:	Not stated			
Batch No.:	Not stated			
Quality:	Niva			
Colour:	Not stated			
Supplier:	Delius GmbH & Co. K	G		
End Use:	Drapes and curtains			
Quoted Fibre Composition:	100% PES Trevira CS			
Retailer:	Not stated			
Buying Division:	Not stated			
Sample Description:	Grey coloured woven fa	abric		

Test Method	Pre Treatment	Performance Requirement	Result
IMO FTP Code (2010) Annex 1, Part 7: Test for Vertically Orientated Support Textiles and Films	None – The scope states that "fabrics which are not inherently flame resistant should be exposed to cleaning or exposure procedures"	IMO FTP Code (2010) Annex 1, Part 7, Clause 3	PASS

Note: The fabric supplied was tested with no pre-treatments at the request of the customer. Please note: The testing was carried out in the ISO 6941 environment

STEVEN OWEN (Technical & Operational Excellence Manager)

ANDREW HALLETT (Flammability Team Leader) CAROLE SPOWART (Flammability Administrator) Report No.: LEI19011658A Supplementary Page 1 of 2









FLAMMABILITY TEST REPORT

Additional Information (Annex) Name and Address of the Sponsor: Name and Address of the Manufacturer/Supplier (If known): Type of Furniture: Fabric Details – Weave/Density/Yarn count/thickness(mm)/mass(g/m ²) Colour &	Not Stated Delius GmbH Not Stated Not Stated
Tone: Fire Retardant Treatment:	No
Test Specification Test Method: Ignition Source: Ignition Type: Flame Application Time: Sample Size: Side Tested:	IMO FTP Code (2010) Annex 1, Part 7 40mm high Propane gas flame Face ignition (as determined by the pre-test) 15 seconds (as determined by the pre-test) 220 x 170mm Face
Pre-treatment / Durability Procedure	

None - At the request of the customer.

Conditioning	
Prior to Testing:	At least 24 hours in an atmosphere having a temperature of 20 ± 5 °C. and a relative humidity of $65\pm5\%$
At Time of Testing:	Temperature between 15°C & 30°C. Relative humidity between 20% & 65%

Test Results

Report of tests carried out in accordance IMO FTP Code (2010) Annex 1, Part 7.

"The test results relate to the behaviour of the test specimens of a product under the particular conditions of the test; they are not intended to be the sole criterion for assessing the potential fire hazard of the product in use."

Sample No./	Duration of	Duration of	Flaming Flame to		Hole to edge	Maximum damaged length (mm)		Average Damage Length (mm)
Direction	flaming (Secs)	afterglow (Secs)	debris	edge		Horizontal	Vertical	Length (mm)
1. Length ↑	0.0	0.0	No	No	No	22	100	
2. Length ↓	0.0	0.0	No	No	No	23	102	
3. Length ↑	0.0	0.0	No	No	No	25	110	107.2
4. Length ↓	0.0	0.0	No	No	No	22	112	
5. Length ↑	0.0	0.0	No	No	No	19	112	
6. Width \rightarrow	0.0	0.0	No	No	No	28	100	
7. Width ←	0.0	0.0	No	No	No	28	90	
8. Width \rightarrow	0.0	0.0	No	No	No	28	118	106.6
9. Width ←	0.0	0.0	No	No	No	22	110	
10. Width \rightarrow	0.0	0.0	No	No	No	27	115	

This report is made solely on the basis of your instructions and/or information and materials supplied by you. It is not intended to be a recommendation for any particular course of action. Intertek does not accept a duty of care or any other responsibility to any person other than the Client in respect of this report and only accepts liability to the Client insofar as is expressly contained in the terms and conditions governing Intertek's provision of services to you. Intertek makes no warranties or representations either express or implied with respect to this report save as provided for in those terms and conditions. We have <u>aimed</u> to conduct the Review on a diligent and careful basis and we do not accept any liability to you for any loss arising out of or in connection with this report, in contract, tort, by statute or otherwise, except in the event of our gross negligence or willful misconduct.

Report No.: LEI19011658A Supplementary Page 2 of 2

