

-"We Test Per Your Request"———

336 WEST FRONT STREET
P.O. BOX 4004
BURLINGTON, NORTH CAROLINA 27215
PHONE (336) 227-7710 • FAX (336) 227-1175
www.diversifiedtestinglabs.com

November 19, 2020

Ms. Angelika Schmidt-Koch DELIUS GMBH & CO. KG Goldstraβe 16 – 18 33602 Bielefeld Germany

Reference:

Laboratory Test Report

Lab Identification No. 43459

Invoice No. 74691

Dear Ms. Schmidt-Koch:

One (1) sample, identified as **Article Ecoline Two Dimout**, was received and tested in accordance with the National Fire Protection Association No. 701, "Standard Methods of Fire Tests for Flame Propagation of Textiles and Films, 2019 Edition, (Test 1)". The results are as follows:

Test Results

| Specimen Number | Residual Flame (seconds) | Weight Loss (percent) |
|-----------------|--------------------------|-----------------------|
| 1 | 0.0 | 14.70 |
| 2 | 0.0 | 12.64 |
| 3 | 0.0 | 12.85 |
| 4 | 0.0 | 14.51 |
| 5 | 0.0 | 16.64 |
| 6 | 0.0 | 15.61 |
| 7 | 0.0 | 12.72 |
| 8 | 0.0 | 14.21 |
| 9 | 0.0 | 14.75 |
| <u>10</u> | <u>0.0</u> | <u>14.84</u> |
| AVG | 0.0 | 14.35 |

The sample submitted **meets** the minimum requirements of the above standard. The average percent weight loss cannot exceed 40% and the weight loss of individual specimens cannot exceed mean value plus three standard deviations. The average residual flame cannot exceed 2.0 seconds.

If there are any questions or when we can be of further assistance, please let us know.

Sincerely,

Brian S. Dement

BSD/mr

